



## SRX-Pro Lite 16 channel 4L1600

i3 Part# 4L1600



### Features

- Compact design
- 16 camera inputs
- Slim DVD-RW
- 16 loop-out video outputs optional
- 2 sensor inputs and 2 control outputs
- Embedded OS
- CMS Support
- Wall-mountable chassis
- Keylock access front panel

### Application & Benefits

The SRX-Pro Lite is an economical 16 channel, 120/100 NTSC/PAL fps recording system that is ideal for remote applications with a large number of installations requiring remote management and event driven recording.

Supporting an Embedded OS, SRX-Pro Lite is extremely secure, reliable and economical.

All SRX-Pro systems are designed to record, search and transmit video, and data transactions while providing event evaluation. As well as a full local graphical user interface, the SRX-Pro Lite makes viewing recorded data and backup to a USB device or the internal DVD-RW fast and easy. The lockable front panel provides easy access to the standard DVD-RW drive, USB 2.0 ports and hard drives.

The SRX-Pro family of products offers seamless remote operation with either i3 Remote Client Software or Internet Explorer 6.0 or higher.

### Recommended Products



L-NSARK-PI  
L-NSARK-PI Pre-  
Installed SATA Box



L-NSAARRK  
L-NSAARRK 2nd SATA  
Back Box




WM-BRK  
WM-BRK Wallmount  
Bracket



1TB-UG  
1TB-UG Additional 1 x 1  
TB Hard Drive -Total  
2TB



IN2TB-UG  
IN2TB-UG Upgrade 1st  
Internal drive to 2TB  
hard drive (from 1TB)



CANADA | 780 Birchmount Road, Unit 16, Scarborough, ON, M1K 5H4  
USA | 1967 Wehrle Drive, Suite 1 Williamsville, NY, 14221

1.866.840.0004  
www.i3international.com

©2014 i3International. The i3 logo is property of i3International Inc. All rights reserved. Specifications, configurations, components and options listed are subject to change without notice.

For design help, accessories or pricing, please contact:  
sales@avsupply or call: 1-858-565-1101



1-800-284-2288 sales@avsupply.com  
www.avsupply.com

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com



# SRX-Pro Lite 16 channel 4L1600

i3 Part# 4L1600

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com

Software Configuration	
Number of analog channels	16
Other IP and megapixel cameras supported	i3international.com
Screen display	1, 4, 6, 9, 10, 13, or 16
Pre-alarm/Post-alarm recording	Yes
Emergency frame rate recording	Yes
Backup video format	i3 Encrypted, AVI, BMP, or JPEG
Number of IP video inputs	Upgradeable to 10 IP Channels
Hardware Configuration	
Operating system	XP Embedded
Standard SATA storage size	1HD w/OS
Max. number of additional HDD	2
Operating devices (CPU, graphics, RAM)	i3 Intel Processor, PCI Express, 2GB RAM DDR 2 or 3
Analog video loop out (75 Ohm, dip switch controlled)	16
VGA resolution requirement	1024 x 768
Number of spot monitors	1
Number sensor in/out (12VDC & 500mA Terminal Blocks)	2/2 [Optional UIO8 = 4/4 (TCP/IP)]
Number of RS485 ports (PTZ)	2 [Optional UIO8 = 1 (TCP/IP)]
Connectivity (LAN/WAN)	1 X 1Gb/sec
Resolution and Compression	
Type of Compression	MJPEG
Analog display speed NTSC/PAL	up to 480/400fps 1CIF
Client Applications	
Remote viewing	IE 6.0, Proprietary Software, & SRX-Pro Player, i3Display
Number of PACDM channels Serial/TCP/IP	Optional Max. 4 lanes serial
CMS (Central Monitoring Software)	Yes
Physical Environment and Certifications	
Type of chassis	Compact Wallmount Steel Alloy
Physical dimensions (LxWxH)	17.125"x13.25"x5.75" (434.98mmx336.55mmx146.05mm)
Power	115-230 VAC, 50-60 Hz, 300 W (auto switch)
Operating temperature & relative humidity	20 - 25C or 68 - 77F < 80%, non-condensing
Certification	UL/ULc, Fcc, CE
Additional Options	
Wall mount bracket	Optional
Expansion wire management box- i3 400E	Optional
Warranty	
Standard Warranty	1 yr parts & 1 yr labour

CANADA | 780 Birchmount Road, Unit 16, Scarborough, ON, M1K 5H4  
 USA | 1967 Wehrle Drive, Suite 1 Williamsville, NY, 14221

1.866.840.0004  
 www.i3international.com

©2014 i3International. The i3 logo is property of i3International Inc. All rights reserved. Specifications, configurations, components and options listed are subject to change without notice. This data sheet may not be reproduced without permission.

For design help, accessories or pricing, please contact:  
 sales@avsupply or call: 1-858-565-1101