



# Di721 Indoor Dome i3 Part# C-Di721



## Features

- 700TVL Sony CCD
- Versatile design for installation
- Vandal resistant dome
- Flush Mountable, Pendant cap included for standard inch fitting
- ATR/Digital-WDR
- Wire management
- i3 Superior 3 year warranty

## Application & Benefits

The new Di721 (indoor) camera comes with Digital Wide Dynamic Range, Day/Night capabilities and vandal-resistant performance. Di721 is backed by i3 International's superior camera warranty through year 2-for-1 return. In case of manufacturer's defects, the customer will receive a brand new, same model, camera along with the repaired original one. Equipped with latest SONY CCD technology, Di721 camera line delivers vivid daytime color and active night image capabilities. This dome line was designed to reduce installation time as mounting adapters for various environments are no longer needed. Rich with practical enhancements, the Di721 dome is ideal for a wide variety of security applications including retail, schools and commercial property.

- Easily accessible convenient control of OSD menu system and features
- Video patch lead enables local image verification on a portable monitor
- Pan-Tilt-Twist (3-axis) gimbal lets installers correct off-center images, even along walls
- Conduit and electrical gang box compatible for easy installations
- Vandal-resistant performance

## Recommended Products



DB60  
DB60 Wallmount Goose  
Neck Camera Bracket



EA24A6-P9  
EA24A6-P9 Power  
Supplies



EA24A12-P18  
EA24A12-P18 Power  
Supplies



UN2412  
UN2412 UTP Power  
Supply



110195  
110195 Single Channel  
Passive Video  
Transceiver



International Standards  
Organization Registered Firm  
ISO 9001 Quality System

CANADA | 780 Birchmount Road, Unit 16, Scarborough, ON, M1K 5H4  
USA | 1967 Wehrle Drive, Suite 1 Williamsville, NY, 14221

1.866.840.0004  
www.i3international.com

© 2014 i3International. The i3 logo is property of i3International Inc. All rights reserved. Specifications, configurations, components and options listed are subject to change without notice.

For design help, accessories or pricing, please contact:  
sales@avsupply or call: 1-858-565-1101



1-800-284-2288 sales@avsupply.com  
www.avsupply.com

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com



## Di721 Indoor Dome

i3 Part# C-Di721

<b>Specifications</b>	
Signal System	NTSC
<b>Image System</b>	
Image Pickup Device	SONY 1/3" Exview HAD CCD II
Effective Pixels (HxV)	976(H) x 494(V)
Angular DOF Range	Pan:350, Tilt:0-60, Rotation:360
<b>Electric</b>	
Scanning System	2:1 Interlace
Scanning System con't	V: 59.94 Hz, H: 15.734 KHz
Sync System	Internal
Horizontal Resolution	700 TV Lines
Built-in Lens	vari-focal, f=2.8mm-10.5mm, F1.2 DC iris
Gamma Correction	0.45
S/N Ratio	More than 50dB (AGC off)
Gain Control (AGC)	On / Off (selectable)
White Balance	ATW/ Manual/ User/ Push/ Push Lock
Electric Shutter	1/60-1/10K sec
Flickerless	Auto adjusted
BLC	OFF/ BLC/ HLC (High Light Compensation) (selectable)
DNR	Yes
Motion Detection	Yes, 4 areas (max)
Privacy Mask	Yes, 8 zones (max)
ATR/D-WDR	Digital Wide Dynamic Range On/Off (Selectable)
OSD	Yes
Multi Language	English, French, Spanish, Portuguese, German, Russian, Simplified Chinese, Japanese
Video Output	1Vpp composite output, 75 ohm
Day/Night Mode	Digital D/N
Minimum illumination	F1.2 @50IRE, 0.02ux, @30IRE, 0.01lux
<b>Power Supply</b>	
Power Requirement	DC 12V & AC 24V +- 10%
Power Consumption	4W (max)
<b>Environment</b>	
Operating Temperature	-10degree C - 50degree C (14 degree F - 122 degree F)
Operating Humidity	90% MAX
Storage Temperature	-20degreeC - 60degreeC (-4degreeF - 140degreeF)
Storage Humidity	70% MAX
Dimensions	140 x 132 mm
<b>Mechanism</b>	
Weight	approx. 573g (1.26 lb)
Protection Class	CE, FCC, Class A, Vandal-Proof
<b>Warranty</b>	
Standard Warranty	i3 Superior 3 year warranty

Distributed By: Audio Video Supply -- Tel: 1-800-284-2288 -- www.avsupply.com

CANADA | 780 Birchmount Road, Unit 16, Scarborough, ON, M1K 5H4  
 USA | 1967 Wehrle Drive, Suite 1 Williamsville, NY, 14221

1.866.840.0004  
 www.i3international.com

©2014 i3International. The i3 logo is property of i3International Inc. All rights reserved. Specifications, configurations, components and options listed are subject to change without notice. This data sheet may not be reproduced without permission.

For design help, accessories or pricing, please contact:  
 sales@avsupply or call: 1-858-565-1101