

# Professional Camera

## 1/3" COLOR CCD high Resolution Color Camera

### CC25NVD-H

- \* 1/3" COLOR CCD High Resolution
- \* 600TVL 0.001 Lux
- \* Digital Wide Dynamic
- \* Super 3-DNR Sense-up 0-128X
- \* Digital WDR OSD Easy Setup
- \* Non-Polarity Power Input
- \* Dual Power DC12V-AC24V 150mA



Lens and Bracket Not Included

Model No.	CC25NVD-H	
Sensor	1/3" Color CCD	
Total Pixels	811(H) x 508(V)	795(H) x 595(V)
Scanning System	768(H) x 494(V)	752(H) x 582(V)
Synchronization	Internal / line lock	
O.S.D	Available	
Dynamic Range	52dB (x128)	
Backlight Compensation	WDR/BLC/OFF Selectable	
Resolution	Color 600TVL (Typ.) 700TVL B/W	
S/N Signal	52dB (AGC OFF , Weight ON)	
Min. Illumination	Color Mode: 0.003(0.6) Lux (Sense-up OFF) B/W Mode:0.0001(0.1) Lux(Sense-up OFF)	
White Balance	ATW/AWC/Manual/Outdoor(1800°K~10.500°K)Indoor(4500°~8500°K)	
Electronic Shutter Speed	1/60sec~1/120000sec	1/50sec~1/120000sec
Sense-up	AUTO/FIXED/OFF (Selectable limit x2~x128)	
Gain Control	LOW/MIDDLE/HIGH/OFF Selectable	
3D-DNR	OFF/ON (1~63 Level Adjustable)	
Motion Detection	ON/OFF (8 Zone / ALARM Output)	
Privacy	ON/OFF (8 Zones)	
Mirror (H- REV)	ON/OFF	
FLIP (V-REV)	ON/OFF	
Freeze	ON/OFF	
Sharpness	ON/OFF (Level Adjustable)	
D&N Selection	Color , B/W , Auto , EXT.	
Stabilizer	ON/OFF	
Digital Zoom	ON(x6) / OFF	
Blemish Compensation	256 Points ( Even 128 Points / Odd 128 Points)	
Iris Control	DC	
Operational Temperature / Humidity	-10°C to +50°C / 30% to 80% RH	
Storage Temperature / Humidity	-20°C to +60°C / 20% to 90% RH	
Dimension	118mm x 50mm x 58mm	
Weight	305g	