

3-Series® Media Presentation Controller 201

- > Wall mount Crestron® 3-Series Control System® and control panel
- > Mounts flush on a wall or lectern
- > Fits in a single-gang European electrical box
- > Retrofit 2-gang US electrical box adapter available
- > Tabletop enclosure available
- > Stylish blue and white backlit capacitive buttons
- > Six buttons customizable with replaceable icon chips
- > Additional power, volume, and mute buttons plus volume gauge
- > Fully-programmable functionality
- > Auto-brightness control
- > Wakes on proximity detection
- > Adjustable key-click sound
- > Enterprise-class 3-Series® control engine
- > Modular programming architecture (optional)^[1]
- > .AV Framework™ system configuration—no programming required!
- > Built-in real-time clock
- > Astronomical time clock for scheduled events
- > High-speed 10/100 Ethernet LAN port
- > Add-on Cresnet® and infiNET EX® interface options
- > Add-on RS-232, IR, relay, and Versiport interface options
- > iPhone®, iPad®, and Android® control app support
- > XPanel computer and web based control with Smart Graphics®
- > Crestron Fusion® room monitoring and scheduling support
- > XiO Cloud™ provisioning and management support
- > SNMP remote IT management support
- > Native BACnet™/IP support^[2]
- > Installer setup via software, web browser, or XiO Cloud
- > Drag-and-drop, C#, and symbol based programming environments
- > Full Unicode (multi-language) support
- > Secure access through full user/group management or Active Directory® integration
- > Hardware level security using 802.1X authentication
- > TLS, SSL, SSH, and SFTP network security protocols
- > FIPS 140-2 compliant encryption
- > Built-in web server and SMTP e-mail client
- > IPv6 ready
- > PoE network powered

The 3-Series® Media Presentation Controller 201 (MPC3-201-B) is a wall-mounted, PoE powered 3-Series Control System® and control panel in one. Its modern appearance and customizable backlit capacitive buttons provide an ideal user-interface for controlling AV and other functions. It offers fully-programmable functionality, supports web and cloud-based configuration and management, and integrates with Crestron Fusion® as part of a complete managed enterprise solution.



Crestron® MPC3 series controllers are perfect for classrooms, meeting rooms, lecture halls, and training facilities – wherever a simple yet powerful controller is needed but space is limited. Use the MPC3-201-B to control a video display or AV system, adjust lighting and window shades, or any other custom application.

The MPC3-201-B is designed for flush-mount installation in a wall using a single-gang European electrical box (not included). It can also be installed in a podium with no back box, or placed on a table using the optional [tabletop kit](#). A [retrofit mounting bracket](#) is also available to allow installation over a 2-gang US electrical box, which offers an easy upgrade solution for replacing an older [MPC-M5](#) series controller.

Customizable Backlit Capacitive Buttons

The MPC3-201-B features six backlit capacitive buttons, which can each be labeled using the icon chips provided, or custom labeled using laser-engravable chips (sold separately). Each button is backlit white when inactive and blue when active to provide clear indication of what media source or lighting scene is currently selected. Four additional buttons are included at the bottom along with a volume gauge for control of volume, mute, and power. A key click sound can be enabled to provide audible assurance when any button is pressed.

All buttons on the MPC3-201-B are custom programmable to control any device or function. Button backlighting can be set to dim or turn off when idle. Built-in proximity sensing wakes the buttons as you approach, and auto-brightness control maintains optimal visibility of the buttons under varying lighting conditions.

Refer to Figure 1 for a list of supplied icon chips. For information about ordering custom icon chips, please refer to the [MPB3/MPC3-BTN3-B ENGRAVED](#) web page.

MPC3-201-B 3-Series® Media Presentation Controller 201

No Rack Required

The MPC3-201-B encapsulates the industry's best control technologies in one compact wall mount device that can alleviate the need for a bulky equipment rack. High-speed Ethernet provides the essential interface for connecting to the building network and controlling Crestron AV switchers, audio processors, and other IP controllable equipment. Expanded connectivity is available using a [DIN-CENCN-2](#) or [DIN-CENCN-2-POE](#) Ethernet to Cresnet® Bridge, [CEN-GWEXER](#) or [CENI-GWEXER](#) inFINET EX® wireless gateway, or [CEN-CI3-1](#) or [CEN-CI3-3](#) control card interface, enabling integration with all types of third-party equipment and the entire line of Crestron lighting controls, motorized shades, sensors, thermostats, door locks, keypads, and more.

3-Series® Control Engine

The MPC3-201-B features an integrated, enterprise-grade 3-Series control processor. Crestron 3-Series delivers a distinctively robust, dynamic, and secure control system platform capable of faithfully managing a room full of disparate technologies. Its Modular Programming Architecture (optional ⁽¹⁾) allows the MPC3-201-B to run multiple programs simultaneously for increased efficiency and flexibility. Rock solid networking and IP control afford seamless integration with other systems and devices, with add-on control capability using Crestron touch screens, wireless remotes, and mobile device apps, and remote management through [Crestron Fusion](#) and [XiO Cloud™](#).

No Programming Required!

Built-in .AV Framework™ technology delivers a fully functional AV presentation system with simplified web-based configuration and a choice of control options and add-ons. For complete details on the capabilities supported by .AV Framework, please visit <https://www.crestron.com/avframework>.

Crestron Fusion® Room Monitoring and Scheduling

Crestron Fusion provides an integrated platform for creating truly smart buildings that save energy, enhance worker productivity, and prolong the life-span of valuable equipment. As part of a complete managed network in a corporate enterprise, college campus, convention center, or any other facility, the MPC3-201-B works integrally with Crestron Fusion to enable remote scheduling, monitoring, and control of rooms and technology from a central help desk or mobile app. It also enables organizations to reduce energy consumption by tracking real-time usage and automating control of AV, lighting, shades, and HVAC. For more information about Crestron Fusion, please visit <https://www.crestron.com/fusion>.

XiO Cloud™ Provisioning and Management

XiO Cloud is Crestron's unifying cloud-based platform for remotely provisioning, monitoring, and managing Crestron devices across an enterprise or an entire client base. XiO Cloud enables installers and IT managers to deploy and manage thousands of devices in the amount of time it would ordinarily take to manage just one. It provides a zero-touch solution that allows complete configuration of device settings without any hardware in hand, then simply connect each device on site and let XiO Cloud push out the settings, licenses, drivers, and firmware updates – automatically and securely – for a quick and painless, ready-to-use deployment.



Ongoing XiO Cloud services facilitate daily management and monitoring of every device through a single dashboard with comprehensive reporting and logging, live status viewing and alerts, performance metrics and analytics, scheduled actions and updates, and more. As requirements grow and evolve, new features and functionality can be added easily to one or many devices at any time without ever going on site. XiO Cloud is a subscription-based service offering an adaptable SaaS (Software as a Service) solution with graduated levels of functionality and unlimited scalability. For more information about XiO Cloud, please visit <https://www.crestron.com/xiocloud>.

Enterprise-Grade Security

The MPC3-201-B is an enterprise-class control processor that can be deployed across hundreds of spaces and set up easily using a web browser, toolbox software, Crestron Fusion, or XiO Cloud. It employs standard network security protocols, including 802.1X network access control, Active Directory® authentication, SSH, TLS, and HTTPS, to ensure reliability and compliance with your organization's IT policies.

SNMP Support

Built-in SNMP support enables integration with third-party IT management software, allowing network administrators to manage and control Crestron systems on the network in an IT-friendly format.

Power over Ethernet

Using PoE technology, the MPC3-201-B gets its operating power right through the LAN wiring. PoE (Power over Ethernet) eliminates the need for a local power supply or any dedicated power wiring. A PoE Injector ([PWE-4803RU](#)) simply connects in line with the LAN cable at any convenient location. Crestron PoE switches ([CEN-SW-POE-5](#) or [CEN-SWPOE-16](#)) may also be used to provide a total networking solution with built-in PoE. All PoE injectors and switches are sold separately.

MPC3-201-B 3-Series® Media Presentation Controller 201

Flush Mount Installation

The MPC3-201-B is designed to be flush-mounted in a wall using a single-gang European electrical box (not included). It can also be installed in a lectern or podium with no back box. Using the optional Retrofit Mounting Bracket ([MPC3-101/102/201-RMB](#) sold separately), the MPC3-201-B can be installed in a 2-gang US electrical box, allowing easy replacement of an existing [MPC-M5](#) series controller. Once installed, the button labels can be changed at any time by simply removing the front cover. A security screw is included to prevent unauthorized removal.

Tabletop Option

Using the optional Tabletop Kit ([MPC3/MPB3-TTK-SQR-B](#) sold separately), the MPC3-201-B becomes a stylish, freestanding controller that fits perfectly on a table, desk, or countertop.

SPECIFICATIONS

Control Engine

Crestron 3-Series; real-time, preemptive multi-threaded/multitasking kernel; transaction-safe extended FAT file system; battery-backed non-volatile real-time clock; supports up to 10 simultaneously running programs (license required^[1]); preloaded .AV Framework base program

Communications

Ethernet: 10/100 Mbps, auto-switching, auto-negotiating, auto-discovery, full/half duplex, TCP/IP, UDP/IP, CIP, DHCP, SSL, TLS, SSH, SFTP (SSH File Transfer Protocol), FIPS 140-2 compliant encryption, IEEE 802.1X, SNMP, BACnet/IP^[2], IPv4 or IPv6, Active Directory authentication, SMTP e-mail client, HTTPS web server, HTTPS web browser setup and XiO Cloud client, IEEE 802.3af & 802.3at Type 1 PoE compliant

Connectors

LAN PoE: (1) 8-pin RJ45 connector, female;
10Base-T/100Base-TX Ethernet port;
PoE PD port

Ground: (1) 6-32 screw;
Chassis ground lug (flying lead with ring terminal included)

Controls & Indicators

Assignable Buttons: (6) Projected capacitive pushbuttons, each may be labeled using one of 25 pre-labeled icon chips or hidden using one of five blackout chips (included), custom laser-etched icon chips are available using optional [MPB3/MPC3-BTN3-B ENGRAVED](#) engravable icon chips (sold separately)

Mute: (1) Projected capacitive pushbutton with “mute” icon
-/+ : (2) Projected capacitive pushbuttons labeled with “-” and “+” icons for volume control

Volume Gauge: (1) Blue LED multi-segment bargraph for volume level indication

Power: (1) Projected capacitive pushbutton labeled with “power” icon

HW-R: (1) Pushbutton (behind front panel) for hardware reset (reboots the processor)

SW-R: (1) Pushbutton (behind front panel) for software reset (restarts the software program)

LAN PoE: (2) LEDs (on rear panel LAN port), green LED indicates Ethernet link status, amber LED indicates Ethernet activity

Illumination: Each capacitive button is individually backlit white when inactive and blue when active; auto-brightness control adjusts all back-lighting in three levels according to the ambient light level; backlighting may be dimmed or extinguished when unit enters idle state

Note: All capacitive buttons are custom programmable

Light Sensor

Photosensor detects the ambient light level to enable auto-brightness control

Proximity Sensor

Type: Eye-safe 940 nm laser ranging sensor
Range: Adjustable from 20 to 90 cm (8 to 35 inches)
Detects bodies within range and wakes the unit from standby or idle state

Audio

Key Click: Sounds when any button is pressed, adjustable to one of three volume settings or off

Power

Power over Ethernet: IEEE 802.3at Type 1 (802.3af compatible) Class 0 (12.95 Watts) PoE Powered Device
Power Consumption: 3 Watts typical

Environmental

Temperature: 5° to 40° C (41° to 104° F)
Humidity: 10% to 90% RH (non-condensing)
Heat Dissipation: 11 BTU/hr

Construction

Housing: Plastic with metal mounting plate, removable front panel with optional security screw

Flush Wall Mount: Mounts in a 1-Gang European (DIN 49073) electrical box (not included), mounts in a 2-gang US electrical box using [MPC3-101/102/201-RMB](#) Retrofit Mounting Bracket (sold separately)

Lectern Mount: Mounts in a 52 mm (2-1/16 inch) square cutout using bracket provided

Tabletop Mount: Sits on a tabletop using [MPC3/MPB3-TTK-SQR-B](#) tabletop kit (sold separately)

Dimensions

Height: 87 mm (3.42 in)
Width: 87 mm (3.42 in)
Depth: 48 mm (1.88 in)

MPC3-201-B 3-Series® Media Presentation Controller 201

Weight

208 g (7.35 oz)

Compliance

CE, IC, FCC Part 15 Class B digital device; Class 1M laser product, complies with safety regulations of IEC- 60825-1, FDA 21 CFR 1040.11, and FDA 21 CRF 1040.10




Figure 1: Included Icon Chips

MODELS & ACCESSORIES

Available Models

MPC3-201-B: 3-Series® Media Presentation Controller 201, Black

Available Accessories

- MPB3/MPC3-BTN3-B ENGRAVED: Backlit Engravable Icon Chips, Black, Set of 3, Includes Custom Engraving
- MPB3/MPC3-BTN3-B BLANK: Backlit Engravable Icon Chips, Black, Set of 3, Engraving Not Included
- SW-RMC3-10PROG: 10 Program MPA Support License
- MPC3-101/102/201-RMB: Retrofit Mounting Bracket
- MPC3/MPB3-TTK-SQR-B: Tabletop Kit, Black
- PWE-4803RU: PoE Injector
- CEN-SW-POE-5: 5-Port PoE Switch
- CEN-SWPOE-16: 16-Port Managed PoE Switch
- SW-XIOC-S Series: XiO Cloud™ Standard Provisioning and Management Service
- SW-XIOC-P Series: XiO Cloud™ Premium Provisioning and Management Service
- SW-FUSION-C-3: Crestron Fusion® Cloud, 250 rooms, 3-year
- SW-FUSION-P-L: Crestron Fusion® On-premises, unlimited rooms, lifetime
- CRESTRON-APP: Crestron® App for iPhone® & iPod touch®
- CRESTRON-APP-ANDROID: Crestron® App for Android®
- CRESTRON-APP-PAD: Crestron® App for iPad®
- XPANEL: XPanel – Crestron Control® for Computers
- SW-3SERIES-BACNET-50+: BACnet™/IP Support for 3-Series®
- DIN-CENCN-2: Ethernet to Cresnet® Bridge
- DIN-CENCN-2-POE: Ethernet to Cresnet® Bridge w/PoE
- CEN-GWEXER: infiNET EX® & ER Wireless Gateway
- CENI-GWEXER: infiNET EX® & ER Wireless Gateway – International Version
- CEN-CI3-1: 3-Series® Card Interface – 1 Slot
- CEN-CI3-3: 3-Series® Card Interface – 3 Slot

Notes:

1. To enable Modular Programming Architecture (MPA) on the MPC3-201-B requires the purchase of one [SW-RMC3-10PROG](#) license. The license enables support for running up to 10 simultaneous programs on a single MPC3-201-B. The license is not required if running only one program. To obtain a license for your MPC3-201-B, please complete the “[Request for SW-RMC3-10PROG License](#)” form. If you have any questions, please send an email to license@crestron.com.
2. BACnet/IP license required. A free license is available to support up to 50 BACnet objects on a single 3-Series control system. A full license must be purchased to enable support for more than 50 objects. The MPC3-201-B supports a maximum of 500 BACnet objects when dedicated for BACnet use only. Actual capabilities are contingent upon the overall program size and complexity. To obtain the license, visit <https://www.crestron.com/bacnetlicense>. For additional information, refer to the [SW-3SERIES-BACNET-50+](#).

MPC3-201-B 3-Series® Media Presentation Controller 201

Crestron, the Crestron logo, 3-Series, 3-Series Control System, .AV Framework, Cresnet, Crestron Control, Crestron Fusion, infiNET EX, Smart Graphics, and XiO Cloud are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. BACnet is either a trademark or registered trademark of American Society of Heating, Refrigerating and Air-Conditioning Engineers, Inc. in the United States and/or other countries. iPad, iPhone, and iPod touch are either trademarks or registered trademarks of Apple Inc. in the United States and/or other countries. Android is either a trademark or registered trademark of Google LLC in the United States and/or other countries. Active Directory is either a trademark or registered trademark of Microsoft Corporation in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice.
©2018 Crestron Electronics, Inc.

