



VS-30FW

3-Port FireWire® 800 Repeater/HUB



The VS-30FW is a high-performance bidirectional hub/repeater for 9-pin FireWire® 800 (IEEE 1394b) signals. It increases the number of ports available and/or extends the distance of FireWire® cable runs.

FEATURES

- **Ports** - 3 bidirectional IEEE 1394b 800Mbps (S800).
- **Range** - Doubles FireWire® cable range from 4.5m (14.75ft) to 9m (29.5ft). Multiple units can be cascaded to extend the range to up to 72m (236ft).
- **Hot Swapping** - Supports Plug and Play.
- **Transfer Rates** - 100, 200, 400 and 800Mbps.
- **ESD Protection** - Incorporates Kramer's Spark-Guard Pro™ signal protection circuitry to help protect against ESD (electrostatic discharge) that can damage digital equipment.
- **Alternate Power Sources** - Can be powered from the 12V DC power supply or through the PC connection.
- **Requires 9-Pin FireWire® 800 Cable.**
- **Compact Kramer TOOLS™** - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.



VS-30FW

TECHNICAL SPECIFICATIONS

PORTS:	3 bidirectional IEEE 1394b 800Mbps (S800) ports.
TRANSFER RATE:	100/200/400/800Mbps (S100, S200, S400, S800).
STANDARDS:	IEEE 1394-1995, IEEE P1394a, IEEE P1394b.
POWER CONSUMPTION:	12V DC, 500mA or from the attached PC.
DIMENSIONS:	12cm x 7.5cm x 2.5cm (4.7" x 2.95" x 0.98") W, D, H.
WEIGHT:	0.3kg (0.67lbs) approx.
INCLUDED ACCESSORIES:	Power supply, FireWire® cable, mounting bracket.
OPTIONS:	RK-3T 19" rack adapter.

